

Power operated pedestrian swing door drive ASSA ABLOY SW200

Holder/Issued to

ASSA ABLOY Entrance Systems AB

Lodjursgatan 10, SE-261 44 Landskrona, Sweden

Product description

SW200, power operated pedestrian swing door drive which is operated by contact or impulse sensor. SW200 can be mounted on the wall on either side of the door for pull or push action and is suitable for hinged single or double doors. To replace a lock with latch bolt a pushing function is required. Battery backup unit is permitted.

SW200 has nine arm systems, models 1007241, 1007965 and 1012012 for push function and models 1007251, 1007247, 1007476, 1008401, 1014729 and 1011998 for pull function. Maximum moment of inertia for the door is 160 kg m² for push and 80 kg m² for pull.

Intended use

The power operated pedestrian swing door drive may only be used for swing doors that have been tested and type approved with or without a lock with latch bolt, in the highest fire resistance classes E 30, A 30 or EI 30. The power operated pedestrian swing door drive is supposed to close the door in the event of a fire, fire alarm or power failure and hold the door in the closed position. It is assumed that type approval for the door is supplemented with the power operated pedestrian swing door drive according to the terms of this type approval.

Trade name

SW200

Approval

The products satisfy the requirements set forth in chapter 8, 4 § 2 PBL, in respect to and under conditions stated in this type approval, and are therefore approved in accordance with the provisions of the following sections of Boverket Building Regulations (BBR) issued by the National Board of Housing, Building and Planning.

Fire resistance class E 30, A 30, EI 30 ¹⁾

5:231

1) Applies only in combination with swing doors that have been tested and type-approved with/without a lock with a latch bolt in the intended fire resistance class. Maximum door size according to tested size. Opening force (holding force) at least 87 N measured at the front edge of the door leaf for doors without a lock. When evacuating, opening forces according to BBR 5:335 apply. In normal use, the opening force at the front edge of the door leaf must not exceed 90 N in the event of a mains power failure or failure of the drive according to SS-EN 16005.

Associated documents

User Manual Swing Door Operator ASSA ABLOY SW200, 1009729- en-8.0, Issue 2021-04-19

Type Approval SC0072-14 | issue 7 | 2025-01-29


RISE Research Institutes of Sweden AB | Certification

Box 857, 501 15 Borås

☎ +46 10 516 50 00 | certifiering@ri.se | www.ri.se

1300214

This document is the property of RISE and may not be reproduced other than in full, except with the prior written approval by RISE



Control

The factory production control (FPC) is monitored by an independent inspection body.
Control plan: Ref no. SC0839-09, SC0072-14 dated 2024-10-15, Inspection body: RISE

When the building proprietor performs inspection at the building site, markings shall be checked to ensure that the correct products have been supplied and that they are used in accordance with the conditions in this type approval and associated documents. Further the product shall be accompanied by a manufacturer's assurance, certifying that the product has been manufactured in accordance with the documents on which this type approval is based.


To keep the fire door in the closed position, the force to push the door open must be at least 87 N measured at an opening angle of 0° at the front edge of the door leaf, for doors without a lock. Measurement of opening forces must be carried out in accordance with SS-EN 17372 at intervals according to the routine for the current occupancy. Information about this control must be found in the instructions for the supervision of escape routes which must be included in the fire protection documentation.

Manufacturing place

Production control includes the following place:
Factory No. 6

Marking

The products are to be marked at the factory. The marking consists of a label on every product supplied and includes:

Holder	ASSA ABLOY Entrance Systems AB, Landskrona
Factory code	Factory No. 6
Product type designation	SW200
Consecutive manufacture no./date of production	no./date
Type approval number	SC0072-14
Boverket's registered trade mark	
RISE Accreditation number	1002
Inspection body	RISE

Basis for approval

Reports no. 3P06849-1 and 3P06849-6 from SP, report no. 353553 from Exova Warringtonfire together with assessment O100408-1245806-1 from RISE.

Drawings according to "List of drawings SW200" dated 2025-01-20.

Comments

In order to avoid the door being accidentally opened in the event of a fire, it is assumed that the following conditions are met:

- That only the elbow contact or push button is used as an impulse device for the door's opening function and that a malfunction does not lead to the door being set up.
- If optical impulse sensors are used, it is assumed that these are disabled by an impulse from a central fire alarm system, separate smoke detectors or otherwise. Smoke detectors must be arranged in such a way that they break the impulse line from the automatic impulse sensor to the door automation, both if they are activated or become de-energized.
- Kill function/emergency function in the power operated pedestrian swing door drive must be activated immediately and not affected by impulse sensors when tenable temperature condition levels are reached according to the Boverket general recommendations (BFS 2011:27) on analytical design of a building's fire protection.

Type Approval SC0072-14 | issue 7 | 2025-01-29

RISE Research Institutes of Sweden AB | Certification

Type Approval and decision on production control

Door with power operated pedestrian swing door drive may only be put into operation when CE marking has been carried out in accordance with the machinery directive/regulation.

If accessible and usable evacuation for people with limited mobility or orientation is required by regulation, any safety sensors need to be disabled by central fire alarm system, separate smoke detectors or otherwise.

Associated documents shall accompany the product or by other means be available to users of the product.

This type approval supersedes the previous type approval with the same number dated 2024-11-14.

Validity

Valid through 2029-11-13.

The validity of this type approval can be verified at RISE homepage.

The validity of this type approval expires when the type approved product with the intended use according to this type approval shall be CE-marked according to the Construction Products Regulation (EU) 305/2011.

A handwritten signature in blue ink, appearing to read 'Stefan Coric'.

Stefan Coric

This is a translation from the Swedish original document. In the event of any dispute as to its content, the Swedish original shall take precedence.